



Interior Preflight		Before Start		Take Off				
Maintenance Status	CHK	Seatbelts / Harness	ON	Carb Heat	OFF			
Weather	CHK	Fuel Selector	BOTH	Mixture	FULL RICH			
AROW Documents	CHK	Mixture	FULL RICH	Throttle	FULL			
Hobbs / Tach Times	LOG	Throttle	1/2 Inch Open	Static RPM's	2200 - 2380			
Control Lock	REMOVE	Beacon	ON	Gauges	GREEN			
Fuel Selector	BOTH	Circuit Breakers	ALL IN	Airspeed	ALIVE			
Ignition Switch	OFF	Avionics Master	OFF	Rotate at 55 KIAS	OK			
Avionics Master	OFF	Prime	AS REQ	Climb		Mesquite (KHQZ)		
Master Switch	ON	Brakes	HOLD	Throttle	FULL	CTAF	123.05	
Flaps	DOWN	Engine Start		60 - 75 KIAS	OK	AWOS	118.17	
Fuel Gauges	CHK	Master Switch	ON	Trim	AS REQ	Elevation	446 MSL	
Lights	CHK	Propeller Area	"CLEAR"	Landing Light	OFF	Runway	17 / 35	
Master Switch	OFF	Ignition Switch	START	Guages	GREEN	Terrell (KTRL)		
Exterior Preflight		Throttle	1000 RPM	Cruise		CTAF	122.80	
		Oil Pressure	GREEN	Throttle RPM's	2300 - 2400	AWOS	119.27	
		Avionics Master	ON	Trim	AS REQ	Elevation	474 MSL	
		Flaps	UP	Mixture	AS REQ	Runway	17 / 35	
		Mixture	LEAN 1 INCH	Gauges	GREEN	Tyler Pounds (KTYR)		
		Transponder	STBY / 1200	H.I. to Compass	SET	Tower	120.10	
		H.I. to Compass	SET	Descent		ATIS	126.25	
		ATIS / AWOS	LISTEN	Mixture	FULL RICH	Elevation	544 MSL	
		Altimeter	SET	Fuel Selector	BOTH	Runway	13/31, 4/22	
		Radio Check	GET	Carb Heat	AS REQ	Sulphur Springs (KSLR)		
		L Wing Leading Edge	OK	Taxi Light	AS REQ	Reduce Power	OK	CTAF
	L Wingtip Lights	OK	Parking Brake	Off	Gauges	GREEN	AWOS	118.35
	L Ailerons	OK	Brakes	TEST	Pre-Landing		Elevation	489 MSL
	L Flaps	OK	Run-Up		Get ATIS / AWOS	OK	Runway	18 / 36
	L Fuel Sump	OK	Position into Wind	OK	Altimeter	SET	McKinney (KTKI)	
	L Wheel/Tire/Brake	OK	Trim for Takeoff	SET	Gauges	GREEN	Tower	118.82
	L Wing Tie-Down	REMOVE	Flight Controls	FREE	Flaps	AS REQ	ASOS	119.92
	Pitot Tube	CLEAR	Instruments	CHK	Lights	AS REQ	Elevation	585 MSL
	L Fuel Quantity	OK	Mixture	FULL RICH	Seatbelts	ON	Runway	17 / 35
	Propeller	OK	Throttle	1700 RPM	Go-Around			
	Nose Wheel/Strut	OK	Vacuum Gauge	4.5" - 5.4"	Pitch	UP	EMERGENCY	
	Engine Cowling	CHK	Oil Temp	GREEN	Power	UP	121.50	
	Alternator Belt	OK	Oil Pressure	GREEN	Clean (Flaps)	UP	FLIGHT WATCH	
	Oil Quantity	6 Min, 7 Max	Ammeter	POS CHARGE	Talk	UP	122.00	
	Nose Fuel Sump	OK	Magnetos	CHK	After Landing			
	R Fuel Quantity	OK	Max Drop	125 RPM	Flaps	UP	All V-Speeds in KIAS	
	R Wing Tie-Down	REMOVE	Max Diff	50 RPM	Mixture	LEAN 1 INCH	Vso	35
	R Wing Leading Edge	OK	Carb Heat	SMALL DROP	Carb Heat	OFF	Vsi	45
	R Wingtip Lights	OK	Throttle	IDLE	Strobes	OFF	Vr	55
	R Aileron	OK	Carb Heat	OFF	Landing Light	AS REQ	Vx	60
	R Flaps	OK	Throttle	1000 RPM	Transponder	STBY / 1200	Vg	65
	R Fuel Sump	OK	Pre-Takeoff		Trim for Takeoff	SET	Vy	75
	R Wheel/Tire/Brake	OK	Flaps	AS REQ	Engine Shut Down		Va	82 - 99
	Fuselage Skin	OK	Mixture	FULL RICH	Music (Avionics Master)	OFF	Vfe	85
	R Tail Leading Edge	OK	Carb Heat	OFF	Mixture	OFF	Vno	127
	R Elevator	OK	H.I. to Compass	SET	Master Switch	OFF	Vne	163
	Trim Tab	OK	Doors / Windows	CLOSED	Magnetos	OFF	Max X-Wind	15
	Rudder	OK	Transponder	ALT / 1200	Hobbs / Tach Times	LOG		
	Tail Tie-Down	REMOVE	Strobe Lights	ON	Control Lock	SET	Mesquite Aviation	
	L Elevator	OK	Scan Area for Aircraft	CHK	Tie downs	ALL	Main:	972-222-3546
	L Tail Leading Edge	OK	Announce Intent	OK	Rudder Gust Lock	INSERT	Josh Sallee:	817-690-3563
	Baggage Door	SECURE	Time Off Note	OK	Windows / Doors	SECURE		



972.222.3546

ENGINE LOSS IN FLIGHT	
Fly The Airplane!!!	
Airspeed (Best Glide)	65 KIAS
Best Field	CHK
Checklist	
Fuel Selector	ON
Mixture	FULL RICH
Throttle	FULL POWER
Carb Heat	ON
Magnetos	BOTH
Primer	IN & LOCKED
Declare Emergency	121.50 / 7700
Execute Landing	CHK

POWER LOSS IMMEDIATELY AFTER TAKEOFF / NO RESTART	
Land Straight Ahead Avoiding Obstacles	
Maintain Best Glide Speed	65 KIAS

IF NO RESTART AND TIME PERMITS	
Fly The Airplane!!!	
Maintain Best Glide Speed	65 KIAS
Squawk	7700
Declare Emergency	121.50
Fuel Selector	OFF
Mixture	FULL LEAN
Seatbelts	SECURE
Flaps	AS REQ
Magnetos	OFF
Master	OFF
Unlatch Door	CHK

ICING	
Pitot Heat	ON
Carb Heat	ON
Cabin Heat & Defrost	ON
Make A 180° Turn	CHK
Descend As Needed	CHK
Increase Engine Speed	CHK
DO NOT LOWER FLAPS!	CHK
Land Faster	CHK

LIGHT GUN SIGNALS		
	On The Ground	In The Air
Steady Green	Clear for Takeoff	Clear To Land
Flashing Green	Clear To Taxi	Return to Land
Steady Red	STOP	Continue Circling
Flashing Red	Taxi Clear of Runway	GO AWAY
Flashing White	Taxi To Parking	N/A
Alternating Green/Red	Use Extreme Caution	

ENGINE FIRE DURING START	
Continue Cranking Starter	
If No Start :	
Mixture	FULL LEAN
Fuel Selector	OFF
<i>Continue Cranking For A Few Seconds</i>	
Evacuate Airplane	OK
Fire Extinguisher	Use if Available
If Start :	
Run A Few Seconds	CHK
Shutdown	CHK
Inspect	CHK

ENGINE FIRE IN FLIGHT	
Mixture	FULL LEAN
Fuel Selector	OFF
Master Switch	OFF
Cabin Heat / Air	OFF
Increase Airspeed	EXTINGUISH FIRE

ELECTRICAL FIRE IN FLIGHT	
All Electrical Devices	OFF
Master Switch	OFF
Close Vents, Cabin Heat & Air	CHK
If Fire Is Out :	
Master Switch	ON
<i>Turn On One Essential Electrical Device At A Time</i>	
<i>Reset Circuit Breakers Only Once If Critical</i>	

CESSNA N1221U	
Fuel Type	100LL
Fuel Capacity	53 Gal Total / 50 Gal Useable
Oil Capacity	7 Qts Max / 6 Qts Min
Tire Pressure	31 PSI-nose / 29 PSI-main
Engine	Lycoming O-320, 150 HP
Electrical	12 Volts, 60-amp
Empty Weight	1442 lbs
Useful Load	858 lbs with no fuel
Max T/O Weight	2300 lbs

